

Reclassification of Non-Confined Space Notice

This form shall be completed and posted at all active entrance to the reclassified confined space.

Equipment Name:		
Equipment Number:		
Location:		
Reclassification Date:		Reclassification Time
Reclassification Team Members	Print	Sign
MPC Safety Representative		
MPC Maintenance Rep.		
Servicing Group Rep.		
Operations Supervision		
Questions		Answers
1.	Continuous atmospheric monitoring shall be required inside the tank.	
2.	Continuous atmospheric monitoring may be required in reclassified excavations based upon work scope.	
FOR TANKS		
3.	A door sheet (approximately 10' x 8') has been cut in the side of the tank.	
4.	The tank has been cleaned and free of residues and materials.	
5.	Additional precautions (PPE, additional continuous monitors, barriers, shields, lighting requirements, rescue equipment, etc.) have been established, as needed.	
FOR EXCAVATIONS		
6.	The excavation has a sufficient protective system (e.g. sloped, benched, or sheeting) and has at least one sloped vehicle ramp (i.e. large enough to support a full sized truck).	
7.	The excavation is located outside active/current unit battery limits.	
8.	To achieve unrestricted entry or egress the excavation has ladders or ramps every 25 feet along the perimeter.	

If the permit space poses no actual or potential atmospheric hazards and if all fall hazards within the space are eliminated, it may be reclassified as long as the hazards remain eliminated.

NOTE: Control of atmospheric hazards through forced air ventilation does not constitute elimination of hazards.