
Blanchard Refining Company LLC	Galveston Bay Refinery	
Title: ME-3A Boom Lift Operator Pre-Use Inspection Checklist	Doc Number: RSW-FORM-000032-GB	Rev No: 2



Equipment Number						
	4 3 JLG 2 1 Start with platform, rotation pins, gate, foot switch and controls in neutral	CAUTION : If any item is found to be in need of repair or in any way unsafe, or contributes to an unsafe condition, report condition immediately to your supervisor. The equipment shall not be operated until it has been restored to safe operating condition. During operation report any unsafe condition immediately to your supervisor.				
:	 Review wear pads, power track, front wheels and side panel for leaks and fluids Review hydraulics and back wheels 	DO NOT ATTEMPT TO MAKE REPAIRS OR ADJUSTMENTS UNLESS SPECIFICALLY AUTHORIZED TO DO SO.				
	Review Emergency controls, fluids and leaks, turntable, front wheel,	For assistance contact the equipment provider.				
	and Power track Review placards, cleanliness, fire extinguisher, frame damage, function check	· · · ·····				
	Prior to operating the boom lift at the work location ensure t	he ME-3C form has been completed.				
	Platform gate, guardrails, foot switch are in place and in good working co	ondition.				
	The manufacturer's operations manual and ANSI standard is stored on the boom lift.					
1	Basket control console switches return to neutral position and are clearly	labeled.				
	All safety devices are operational and have not been bypassed.					
	Emergency switch allowing control to go from platform to ground, & hydr	aulic or battery operating properly.				
	Emergency stop & emergency lowering devices function properly.					
	Rotation bolts are all secure.					
2	Wear pads and bolts are not worn down.					
	Front drive hub and tires in good condition.					
	Battery indicator shows an acceptable level remaining. (If applicable)					
	Oil supply and breather at acceptable level and condition.					
3	Rear drive hubs and tires in good condition.					
3	Hydraulics in good condition.					
	Limit Switch secure.					
	Power Track secure.					
	Turn table lock.					
	Hydraulic level is acceptable and the system is not leaking.					
4	Fuel level is acceptable and the system is not leaking.					
	No obstructions to turn table gears.					
	Rental company maintenance sticker by controls.					
	Annual inspection sticker on equipment for validation. All manufacturer required inspections of all hydraulic control relief					
	All safety indicator lights work properly and motion alarms are functional.					
	No loose or missing parts. (Bolts, fasteners, braces, bracket, etc.)					
	Operator knows rated capacity for this equipment?					
	Other personal protective devices are in good condition (Fall restraint anchor points).					
5	No defects such as cracked welds, damaged control cables, damaged wire harness or other obvious damage.					
	Work platform is clean, dry and clear of debris and there is no equipment attached (Air hoses, welding leads, etc.).					
	Stabilizers, outriggers and/or extending axles function properly (If applicable).					
	Drive motor brake/braking devices are operating properly.					

Printed 10/16/2023RSW-FORM-000032-GB.docxPage 1 of 2Printed copies should be used with caution.The user of this document must ensure that the current approved version of the
document is used.

Blanchard Refining Company LLC	Galveston Bay Refinery	
Title: ME-3A Boom Lift Operator Pre-Use Inspection Checklist	Doc Number: RSW-FORM-000032-GB	Rev No: 2

By signing below, you are affirming that you have completed all items listed on page 1 of this checklist.

DATE	PRINT NAME	SIGNATURE	COMPANY

Send completed card to MPC garage. This checklist must be maintained for 30 days after the last date on form. Only trained and qualified operators are allowed to operate equipment.